

1 - NOTES ON THE PRODUCT

STORAGE

DoTile® Fit MAGNITUDO doesn't have particular storage contraindications.

Temperatures below 10°C can stiffen the rubber parts, making them more difficult to handle.

Avoid the installation with temperatures below than 5°C.

Before proceeding with the installation, let stand the tiles for at least 5 days from the indicated date of manufacture

2 - TOOLS

- Rubber mallet.
- 3mm hex key.

Make sure you have the tools before starting the installation.

3 – SURFACE PREPARATION

Thoroughly inspect the levels homogeneity.

The surface must be mechanically resistant, free of loose material, without any roughness, free from grease, oil, paint, wax, etc. and sufficiently dry.

4 – SIZE CHECK

The dimensional tolerance on the rubber tiles is equal to +/- 1%. Further changes can be due to:

- Elastic compression of the packed tiles.
- Thermal expansion due to external

temperature.

To minimize the problem of size variations, it is suggested to:

- Lay the tiles in a continuous manner avoiding interruptions that may increase the risk of different environmental conditions.
- Remove the product from the pallet and place it on the ground 24 hours before installation.
- Avoid the installation with temperatures below than 5°C.
- Complete the installation in a single continuous session avoiding long interruptions, to guarantee constant ambiental conditions.

5 – INSTALLATION

5.1 Installation

Lay the tiles inside the adjustable metal frame, which once fixed will ensure the surface cohesion.

The tile's color could vary, since these are made of reclaimed materials.

5.2 Adjustable Metal Frame

The adjustable metal frame is composed by four squared-section edges and four adjustable corners, which can be fixed by means of TPS EI 5x15 screws, provided inside the kit.

With each screw must be used a flat washer to allow a correct assembly. The screws must be fixed with a 3mm hex key.

6 – SURFACE MAINTENANCE

DoTile® Fit MAGNITUDO doesn't require special maintenance measures, since the materials are stable over the time. All components are wear resistant and resistant to mold and bacteria.

It is possible to wash the surface with normal detergents for floorings or sanitizing products. Cleaning with hot water and soap is the best way to wash away any greasy or oily substance.

The commonly used cleaning methods for this surface are:

- broom or vacuum cleaner.
- damp cloth.
- scrubbing machine.

7 – RESPONSABILITY

The installation guidelines presented in this document represent a typical case.

Metem disclaims any liability for any damage or injury resulting directly or indirectly from improper or inadequate installation.

GUARANTEE TERMS

Metem srl, hereinafter referred as the "Producer".
DoTile® Fit MAGNITUDO hereinafter referred as
the "Product".

The Producer declares that:

a. The offered warranty period is equal to the statutory warranty, starting from the delivery date of the Product on the place of installation.

b. That the Product complies with the technical data sheets and the technical publications provided by the producer during the sale.

c. That the Product complies with the following features:

- the wear of the floor will not exceed 2 mm per year, even in case of intensive use of the area.

The full colored granules ensures that the coloring of the tiles will always remain homogeneous and free of stains.

- The product complies with the declared regulations.

d. In case of justified defect, about the characteristics mentioned above, the Producer will fully implement its obligations of warranty replacement of the defective product.

This warranty covers only the materials. The Producer is not liable for product damage during transport and installation.

Decay conditions of the Producer's warranty:

a. The Product presents partial or whole defects, due to the installation not in accordance with installation instructions.

b. The Product has been installed on a surface whose characteristics are not conform to what is stated in the installation instructions.

c. The Product has been subjected to improper use, cleaned with strong chemicals or subjected to other treatments not approved by the manufacturer.

d. Alterations or repairs made without prior consultation and authorization from the Producer.

e. Purchaser's decision to deny the access to the Producer on the installation area for testing purposes or supervision of the siting, during the warranty period.

f. In case of a claim for defects caused by negligence, abuse, vandalism, accidents.

g. In case of a claim for defects caused by natural disasters.

h. If the buyer doesn't respect the terms and conditions mentioned in this document.

i. If the buyer doesn't comply with the payment of the purchased product.